

LW 5111-TRI 4 WAY COAXIAL

Discontinued products

BASS:	2 x 18" bass loudspeakers LW6115LF
	4 x 10" midrange loudspeakers LW5009MF
MID:	COAXIAL driver $1 \times 1,75$ " high range + $3,5$ " mid-high
	range with inside passive filter
TREBLE:	70° x 40° mid/mid-high/high LW5011HFD with
	pan/tilt adjustment
HORN:	80+150+800+1500W AES. Nominal impedance
	8+8+8 ohm.
POWER:	LF unit:
	Sens 102dB/1W/1m. Half space
	SPL 133,8dB.
	MF unit:
	Sens 101dB/1W/1m. Free field
	SPL 130dB
	HF unit:
	Sens 118dB/1W/1m. Free field
	SPL 141,6dB
SENSITIVITY:	(-10dB) 33,48 Hz-22.000 Hz. Use 200/300Hz and
	1700/2000 for tri-amp.
FREQUENCY	660 x 2670 x 603 cm.
With built-in netwo	ork for mid/high 2x18" bass speakers + 4x10" midrange

With built-in network for mid/high. 2x18" bass speakers + 4x10" midrange speakers + the new coaxial driver 1x3,5" mid-high + 1,75" high treble. With a big aiming device for the medium/bass, medium/treble and treble unit. The coaxial driver delivers uniform high frequency without cancellations for a

perfect vocal intelligibility.

This state-of-the-art unit, manufactured with our best components, is one of our best achievements to deliver the highest quality for the best and biggest flagship cinemas.

All of the eight transducers are in phase. To save labour costs, it is delivered pre assembled in two cartons.



